Quickwall

OWK

Create a display on the fly with this easy to assemble, affordable 10' backwall solution including three Retractor 2 banner stands and a compact, hard molded OCB case.



We are continually improving and modifying our product range and reserve the right to vary the specifications without prior notice. All dimensions and weights quoted are approximate and we accept no responsibility for variance. E&OE. See Graphic Templates for graphic bleed specifications.

features and benefits:

Includes three Retractor 2's

- One Retractor 2 comes complete with base, pole, toprail and bag
- Swivel foot base
- Snap graphic toprail
- 90 day hardware warranty against manufacturer defects

Includes OCB case

- Hard molded, heavy duty banner stand shipping case
- Carry strap included
- Made from 100% recyclable materials
- Variable height
- Protective foam padding
- Made in the USA

dimensions:

aimensions:	
Hardware	Graphic
One Retractor 2: 33" w x 14.5"d x 83.75"h 838.2mm(w) x 368.3mm(d) x 2127.25mm(h)	One Retractor 2: 31"w x 77.5"h plus 1/2" bleed at the top and 6" bleed at the bottom
Assembled unit: 97"w x 20"d x 83.75"h approx. 2463.8mm(w) x 508mm(d) x 2127.25mm(h)	Refer to related graphic template for more information
Assembled unit dimension may vary based on angle of stands	

Shipping

Shipping dimensions - ships in one box Each box: 40"l x 17"w x 7"h 1016mm(l) x 431.8mm(w) x 178mm(h)

Approximate shipping weight: 35lbs/16kg

additional information:

Graphic materials: 13 oz flatmaxx vinyl or oxford fabric

Recomended spacing: 1.5" between graphics, slightly angled outer stands

Stands are supplied with both clamp and adhesive rails, we recommend use of clamp rail with Quickwall system

Quickwall Set-Up






Remove pole from pole compartment in the base of each stand



Swivel the stabalizing feet all the way out to steady bases 3



Assemble three piece bungee poles






Gently lean each unit back and pull the graphic up by the hook 6



Place hook in top of pole to secure graphics



Installing a Graphic



Use clamp rail - open graphic rail and insert graphic into slot



firmly press down on rail to close and secure graphic




Pull attached leader strip all the way out and push pin in side of base to secure - remove paper backing from the tape on the leader strip



Attach bottom of the back side of graphic to the tape on leader strip

Installing a Graphic Cont'd.





Holding the rail, slowly retract graphic into the base

OCB Adjustable Case

